



AC90 & ISO-AC90 600V CSA FT4-ST1 LSZH

AC90	Part No.	Power Conductor		Ground Conductor	Insulation Thickness		Armour O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
		Count	AWG	AWG	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
8021402	2	14	14	0.030	0.76	0.430	10.9	81	120	66	30	6.0	151	25	
8021202	2	12	14	0.030	0.76	0.454	11.5	99	148	104	47	6.4	164	30	
8021002	2	10	12	0.030	0.76	0.512	13.0	138	206	166	75	6.9	174	40	
8021403	3	14	14	0.030	0.76	0.445	11.3	105	156	99	45	6.2	158	25	
8021203	3	12	14	0.030	0.76	0.490	12.4	130	193	157	71	6.9	174	30	
8021003	3	10	12	0.030	0.76	0.535	13.6	182	271	249	113	7.5	190	40	
8030803	3	8/7	10	0.045	1.14	0.714	18.1	309	460	418	190	10.0	254	55	
8030603	3	6/7	8/7	0.045	1.14	0.770	19.6	417	621	702	318	10.8	274	75	
8030403	3	4/7	8/7	0.045	1.14	0.940	23.9	601	894	1193	541	13.2	334	95	
8030303	3	3/7	6/7	0.045	1.14	0.990	25.1	721	1073	1622	736	13.9	352	115	
8030203	3	2/7	6/7	0.045	1.14	1.040	26.4	891	1326	1922	872	14.6	370	130	
8021404	4	14	14	0.030	0.76	0.490	12.4	130	193	131	60	6.9	174	20	
8021204	4	12	14	0.030	0.76	0.535	13.6	166	247	209	95	7.5	190	24	
8021004	4	10	12	0.030	0.76	0.630	16.0	232	345	332	150	8.8	224	32	

ISO-AC90	Part No.	Conductor Count	Power Conductor	Ins. Ground Conductor	Ground Conductor	Insulation Thickness		Armour O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	AWG	AWG	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
8001402	2	14	14	14	0.030	0.76	0.440	11.2	105	156	66	30	6.2	157	25	
8001202	2	12	12	14	0.030	0.76	0.485	12.3	138	206	104	47	6.8	173	30	
8001002	2	10	10	12	0.030	0.76	0.533	13.5	186	277	166	75	7.5	190	40	
8001203	3	12	12	14	0.030	0.76	0.535	13.6	165	245	157	71	7.5	190	24	
8001003	3	10	10	12	0.030	0.76	0.591	15.0	232	346	249	113	8.3	210	32	

Ampacity values based on CEC Part I 2018, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 51, Armoured Cables (Type AC90)
- CSA C22.2 No. 38 Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 2556 FT4-ST1 Vertical-Tray Flame Test
- -40°C Cold Bend and -40°C Cold Impact
- HALOGEN-FREE

- Conductor** Solid Soft Bare Copper Conductors, ASTM B3 8-2 AWG - Stranded Bare Soft Copper, ASTM B8
- Insulation** Cross-linked Polyethylene Insulation (XLPE) CSA Type XL 90°C dry/wet 600V
- Bonding** Solid Soft Bare and Insulated Copper Conductor
- Armour** Aluminum or Galvanized Steel Interlock Armour
- Colour Code** Black, White, Red, Blue and Green for Insulated Ground – Pairs are Black and White

Applications

- For exposed or concealed wiring in dry locations only.
- Use in ventilated, non-ventilated and ladder-type cable trays or service entrance above ground.
- ISO-AC90 is also recommended for single-phase isolated wiring systems, refer to CEC Part I 2018 Rules 24-102 and 24-104.