



4 Conductor TECK90 1000V CSA FT4

4C	Part No.	Power Conductor	Bonding Conductor	Insulation Thickness		Inner Jacket O.D.		Armour O.D.		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
		AWG/kcmil	AWG	in	mm	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
T1XAAUS4-4C-AL	4	6	0.060	1.52	0.968	24.59	1.223	31.07	1.307	33.21	685	1019	801	363	18.3	465	60	
T1XAAUS2-4C-AL	2	6	0.060	1.52	1.104	28.04	1.359	34.52	1.443	36.65	854	1270	1275	579	20.2	513	80	
T1XAAUS1-4C-AL	1	4	0.080	2.03	1.290	32.76	1.545	39.24	1.645	41.78	1097	1632	1607	729	23.0	585	92	
T1XAAUS1/0-4C-AL	1/0	4	0.080	2.03	1.380	35.06	1.635	41.54	1.735	44.08	1236	1840	2029	921	24.3	617	108	
T1XAAUS2/0-4C-AL	2/0	4	0.080	2.03	1.391	35.32	1.646	41.80	1.746	44.34	1367	2033	2556	1160	24.4	621	120	
T1XAAUS3/0-4C-AL	3/0	4	0.080	2.03	1.485	37.71	1.740	44.19	1.840	46.73	1550	2306	3224	1463	25.8	654	140	
T1XAAUS4/0-4C-AL	4/0	2	0.080	2.03	1.788	45.41	2.098	53.29	2.198	55.83	1979	2945	4064	1844	30.8	782	164	
T1XAAUS250-4C-AL	250	2	0.090	2.29	1.943	49.36	2.253	57.24	2.383	60.54	2380	3542	4802	2178	33.4	848	184	
T1XAAUS350-4C-AL	350	2	0.090	2.29	2.180	55.38	2.490	63.25	2.620	66.56	2955	4397	6722	3049	36.7	932	224	
T1XAAUS500-4C-AL	500	1	0.090	2.28	2.477	62.91	2.787	72.40	2.917	75.40	3789	5637	9603	4356	40.8	1056	280	
T1XAAUS750-4C-AL	750	1/0	0.090	2.28	2.951	74.95	3.261	82.40	3.405	85.70	5351	7961	14405	6534	47.7	1200	348	

Ampacity values based on CEC Part I 2018, Table 4 and 5C. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 131, Type TECK90 cable
- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 2556 FT4 Vertical-Tray Flame Test
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant, SUN RES and Low Acid Gas, AG14

Conductor Stranded AA-8000 Series Aluminum Alloy (ACM)

Insulation Cross-linked Polyethylene Insulation (XLPE)
CSA Type XL 90°C dry/wet 1000V

Bonding Stranded AA-8000 Series Aluminum Alloy (ACM)

Armour Aluminum Interlock Armour

Jacket Low Acid Gas Polyvinyl Chloride (PVC)
Inner and Outer Jackets

Colour Code Black, White, Red & Blue or
Black with White Numbering

Applications

- For wet and dry locations.
- To be used for exposed and concealed wiring or where subjected to the weather.
- For direct earth burial and service entrance above or below ground.
- Use in ventilated, non-ventilated and ladder-type cable trays.

CUSTOM ORDER OPTIONS

