

FT 4Tinned Copper
600V**ElectroCom®**AWM
600V

CL3

FLAME
RATINGLOW
TEMPHIGH
TEMPEXPOSED
WIRING**14 AWG FT4 600V - Overall Shielded Multi-Conductors**

Multi	Part No.	Conductor Count	Insulation Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
			in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
	5151402TFT4	2	0.015	0.38	0.262	6.7	48	72	68	31	3.7	93
	5151403TFT4	3	0.015	0.38	0.278	7.1	66	98	102	46	3.9	99
	5151404TFT4	4	0.015	0.38	0.305	7.7	84	124	137	62	4.3	108
	5151405TFT4	5	0.015	0.38	0.335	8.5	98	146	171	77	4.7	119
	5151407TFT4	7	0.015	0.38	0.400	10.2	135	201	239	108	5.6	142
	5151409TFT4	9	0.015	0.38	0.450	11.4	171	254	307	139	6.3	160
	5151415TFT4	15	0.015	0.38	0.559	14.2	284	422	512	232	7.8	199
	5151425TFT4	25	0.015	0.38	0.680	17.3	447	665	854	387	9.5	242
	5151430TFT4	30	0.015	0.38	0.779	19.8	546	813	1025	465	10.9	277

*Dimensions and weights are nominal and subject to change without notice.***Specifications and Compliances**

- UL 13, Power Limited Circuit Cables (CL3)
- CSA C22.2 No. 210, Appliance Wiring Material (AWM I/II A/B)
- CSA C22.2 No. 2556/ UL1685, Vertical-Tray Flame Test

Conductor	Stranded Tinned Soft Copper, ASTM B33
Insulation	Polyvinyl Chloride (SRPVC), 105°C
Shielding	Overall Shield with Tinned Copper Drain Wire
Jacket	Polyvinyl Chloride (PVC)

Applications

- For use in internal wiring of electronic equipment and appliances and power limited circuits where not subject to mechanical damage.
- For wiring under raised floors as per CEC Part I 12-020 and NEC 725.154(A).
- For Class 3 (NEC) and Class 2 circuits as described in NEC Article 725 and CEC Part I.



055-R5

**Electro**
cables

Innovation in Connecting Technology