

FT 4
Tinned Copper
600V

ElectroCom®



24 AWG FT4 600V - Unshielded Multi-Conductors

Multi	Part No.	Conductor Count	Insulation Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
			in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
	6102402TFT4	2	0.010	0.25	0.121	3.1	7	11	6	3	1.7	43
	6102403TFT4	3	0.010	0.25	0.136	3.5	11	16	10	4	1.9	48
	6102404TFT4	4	0.010	0.25	0.147	3.7	13	20	13	6	2.1	52
	6102405TFT4	5	0.010	0.25	0.160	4.1	16	23	16	7	2.2	57
	6102406TFT4	6	0.010	0.25	0.172	4.4	19	29	19	9	2.4	61
	6102407TFT4	7	0.010	0.25	0.184	4.7	21	31	23	10	2.6	65
	6102408TFT4	8	0.010	0.25	0.201	5.1	24	35	26	12	2.8	71
	6102409TFT4	9	0.010	0.25	0.212	5.4	28	41	29	13	3.0	75
	6102410TFT4	10	0.010	0.25	0.226	5.7	31	46	32	15	3.2	80

Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 214/UL 444, Communication Cables (Type CMG)
- CSA C22.2 No. 210, Appliance Wiring Material (AWM I/II A/B)
- CSA C22.2 No. 2556/ UL1685, Vertical-Tray Flame Test (CMG FT4)

Applications

- For use in communication and power limited circuits where not subject to mechanical damage.
- For wiring under raised floors as per CEC Part I 12-020 and NEC 725.154(A).

Conductor Stranded Tinned Soft Copper, ASTM B33
Insulation Polyvinyl Chloride (SRPVC), 105°C
Jacket Polyvinyl Chloride (PVC)