



## 16 AWG FT4 600V - Unshielded Multi-Conductors

Multi	Part No.	Conductor Count	Insulation Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
			in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
			6101602TFT4	2	0.015	0.38	0.228	5.8	28	42	26	12
6101603TFT4	3	0.015	0.38	0.236	6.0	42	62	39	18	3.3	84	
6101604TFT4	4	0.015	0.38	0.249	6.3	54	80	52	23	3.5	89	
6101605TFT4	5	0.015	0.38	0.283	7.2	63	94	65	29	4.0	101	
6101606TFT4	6	0.015	0.38	0.316	8.0	77	115	78	35	4.4	112	
6101607TFT4	7	0.015	0.38	0.328	8.3	89	132	91	41	4.6	117	
6101608TFT4	8	0.015	0.38	0.366	9.3	102	152	104	47	5.1	130	
6101609TFT4	9	0.015	0.38	0.378	9.6	113	168	116	53	5.3	134	
6101612TFT4	12	0.015	0.38	0.413	10.5	144	214	155	70	5.8	147	
6101615TFT4	15	0.015	0.38	0.481	12.2	188	280	194	88	6.7	171	
6101619TFT4	19	0.015	0.38	0.570	14.5	237	352	246	112	8.0	203	
6101620TFT4	20	0.015	0.38	0.580	14.7	247	367	323	147	8.1	206	
6101625TFT4	25	0.015	0.38	0.635	16.3	320	476	720	327	8.9	228	

Dimensions and weights are nominal and subject to change without notice.

### Specifications and Compliances

- CSA C22.2 No. 214/UL 444, Communication Cables (Type CMG)
- CSA C22.2 No. 210, Appliance Wiring Material (AWM I/II A/B)
- CSA C22.2 No. 2556/ UL1685, Vertical-Tray Flame Test (CMG FT4)

**Conductor** Stranded Tinned Soft Copper, ASTM B33

**Insulation** Polyvinyl Chloride (SRPVC), 105°C

**Jacket** Polyvinyl Chloride (PVC)

### Applications

- For use in communication and power limited circuits where not subject to mechanical damage.
- For wiring under raised floors as per CEC Part I 12-020 and NEC 725.154(A).