



14 AWG FT4 600V - Unshielded Multi-Conductors

Multi	Part No.	Conductor Count	Insulation Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
			in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
	6101402TFT4	2	0.015	0.38	0.227	5.8	40	59	68	31	3.2	81
	6101403TFT4	3	0.015	0.38	0.278	7.1	61	91	102	46	3.9	99
	6101404TFT4	4	0.015	0.38	0.295	7.5	74	110	137	62	4.1	105
	6101405TFT4	5	0.015	0.38	0.353	9.0	97	145	171	77	4.9	126
	6101407TFT4	7	0.015	0.38	0.372	9.4	128	191	239	108	5.2	132
	6101409TFT4	9	0.015	0.38	0.450	11.4	167	249	307	139	6.3	160
	6101412TFT4	12	0.015	0.38	0.471	12.0	213	317	410	186	6.6	167
	6101415TFT4	15	0.015	0.38	0.551	14.0	266	396	512	232	7.7	196

Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- UL 13, Power Limited Circuit Cables (CL3)
- CSA C22.2 No. 210, Appliance Wiring Material (AWM I/II A/B)
- CSA C22.2 No. 2556/ UL1685, Vertical-Tray Flame Test

Conductor Stranded Tinned Soft Copper, ASTM B33
Insulation Polyvinyl Chloride (SRPVC), 105°C
Jacket Polyvinyl Chloride (PVC)

Applications

- For use in internal wiring of electronic equipment and appliances and power limited circuits where not subject to mechanical damage.
- For wiring under raised floors as per CEC Part I 12-020 and NEC 725.154(A).
- For Class 3 (NEC) and Class 2 circuits as described in NEC Article 725 and CEC Part I.

