



## 4 Conductor RWU90 1000V CSA

4C	Part No.	Conductor Size	Cable O.D.		Cable Weight		Max Pulling Tension		Resistance at 25°C	Ampacity
		AWG/kcmil	in	mm	lbs/Mft	kg/km	lbs	kg	Ω/Mft	A
	9140604	6	0.762	19.34	206	307	503	228	0.661	44
	9140404	4	0.899	22.83	285	423	801	363	0.416	60
	9140304	3	0.964	24.49	338	502	1010	458	0.327	68
	9140204	2	1.036	26.32	403	600	1275	578	0.261	80
	9140104	1	1.181	30.01	527	784	1606	729	0.207	92
	91401/004	1/0	1.285	32.63	630	937	2029	920	0.165	108
	91402/004	2/0	1.366	34.71	752	1119	2556	1159	0.130	120
	91403/004	3/0	1.422	36.12	896	1333	3223	1462	0.103	140
	91404/004	4/0	1.636	41.56	1112	1654	4064	1844	0.079	164
	91425004	250	1.820	46.22	1370	2038	4800	2177	0.067	184
	91435004	350	2.051	52.09	1825	2716	6720	3048	0.050	224
	91450004	500	2.316	58.83	2490	3705	9600	4355	0.035	280
	91460004	600	2.594	65.88	3018	4491	12800	5806	0.029	308
	91475004	750	2.848	72.33	3678	5473	14400	6532	0.023	348

Ampacity values based on CEC Part I 2018, Table 4 and 5C. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

### Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RWU90)
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant SUN RES

**Conductor** Stranded AA-8000 Series Aluminum Alloy (ACM)

**Insulation** Cross-linked Polyethylene Insulation (XLPE) CSA Type XL 90°C dry/wet 1000V

**Assembly** Cabled without a bonding conductor

**Colour Code** Black, Red, Blue and White or Black with Coloured Stripe

### Applications

- For exposed wiring and raceways (except cable tray) in wet and dry locations.
- For direct earth burial (with protection as required by inspection).
- Minimum recommended installation temperature of minus 40°C with proper handling procedures.
- Cables marked SUN RES are also for outdoor use and exposed wiring subjected to the weather.