



## 12 AWG RW90 600V CSA FT4 TC-ER

12 AWG	Part No.	Conductor Count	Bonding Conductor	Insulation Thickness		Jacket Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	
	8201202BBG-P4E	2/C	12	0.030	0.8	0.045	1.1	0.414	10.5	116	173	104	47	3.7	95	30
	8201203BBG-P4E	3/C	12	0.030	0.8	0.045	1.1	0.436	11.1	146	217	156	71	3.9	100	30
	8201204BBG-P4E	4/C	12	0.030	0.8	0.045	1.1	0.476	12.1	177	263	208	94	4.3	109	24
	8201205BBG-P4E	5/C	12	0.030	0.8	0.06	1.5	0.549	14.0	227	338	260	118	4.9	126	24
	8201206BBG-P4E	6/C	12	0.030	0.8	0.06	1.5	0.568	14.4	258	384	313	142	5.1	130	24
	8201207BBG-P4E	7/C	12	0.030	0.8	0.06	1.5	0.595	15.1	289	430	365	166	5.4	136	21
	8201208BBG-P4E	8/C	12	0.030	0.8	0.06	1.5	0.64	16.3	323	481	417	189	5.8	146	21
	8201209BBG-P4E	9/C	12	0.030	0.8	0.06	1.5	0.663	16.8	354	527	469	213	6.0	152	21
	8201210BBG-P4E	10/C	12	0.030	0.8	0.06	1.5	0.692	17.6	386	574	521	236	6.2	158	21
	8201211BBG-P4E	11/C	12	0.030	0.8	0.06	1.5	0.717	18.2	417	620	573	260	6.5	164	21
	8201212BBG-P4E	12/C	12	0.030	0.8	0.06	1.5	0.743	18.9	448	667	625	283	6.7	170	21
	8201215BBG-P4E	15/C	12	0.030	0.8	0.08	2.0	0.869	22.1	577	859	781	354	7.8	199	21
	8201220BBG-P4E	20/C	12	0.030	0.8	0.08	2.0	0.983	25.0	736	1096	1042	473	8.8	225	21
	8201225BBG-P4E	25/C	12	0.030	0.8	0.08	2.0	1.088	27.6	894	1331	1302	591	9.8	249	18
	8201230BBG-P4E	30/C	12	0.030	0.8	0.08	2.0	1.154	29.3	1048	1560	1563	709	10.4	264	18
	8201240BBG-P4E	40/C	12	0.030	0.8	0.08	2.0	1.289	32.7	1353	2013	2084	945	11.6	295	18
	8201250BBG-P4E	50/C	12	0.030	0.8	0.08	2.0	1.431	36.3	1658	2467	2605	1182	12.9	327	15

Ampacity values based on CE Code Part I 2021, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

### Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 230, Tray Cables Extended run
- CSA C22.2 No. 2556 FT4, IEEE 1202/UL 1685 Vertical-Tray Flame Test
- -40°C Cold Bend and -40°C Cold Impact
- SUN RES all colours

<b>Conductor</b>	Stranded Bare Soft Copper, ASTM B8
<b>Insulation</b>	Cross-linked Polyethylene Insulation (XLPE) CSA Type XL 90°C dry/wet 600V
<b>Jacket</b>	Low Acid Gas Polyvinyl Chloride (PVC)
<b>Colour Code</b>	Black, White, Red and Blue or Black with White printed number
<b>Bonding</b>	Green Insulated Stranded Bare Soft Copper, ASTM B8

### Applications

- For wet and dry locations.
- For use in raceways, including cable trays, Ventilated, non-ventilated, ladder tray and direct burial.
- To be used for exposed and concealed wiring or where subjected to the weather.
- For Hazardous Locations Class I-Zone 0 Intrinsically safe Div. 2, Class II-Zone 2 Div. 2 and Class III-Div. 2.
- Cables marked TC-ER tray cable are permitted to transition between cable trays, and utilization equipment or devices as per CE Code Part I 12-2202 2) and 3).



### CUSTOM ORDER OPTIONS

