



10 AWG RW90 600V CSA FT4 TC-ER

10 AWG	Part No.	Conductor Count	Bonding Conductor	Insulation Thickness		Jacket Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	
	8201002BBG-P4E	2/C	10	0.030	0.8	0.045	1.1	0.462	11.7	162	242	166	75	5.5	141	40
	8201003BBG-P4E	3/C	10	0.030	0.8	0.045	1.1	0.488	12.4	206	307	249	113	5.9	149	40
	8201004BBG-P4E	4/C	10	0.030	0.8	0.060	1.5	0.564	14.3	268	399	332	151	6.8	172	32
	8201005BBG-P4E	5/C	10	0.030	0.8	0.060	1.5	0.614	15.6	320	477	415	188	7.4	187	32
	8201006BBG-P4E	6/C	10	0.030	0.8	0.060	1.5	0.635	16.1	365	543	498	226	7.6	194	32
	8201007BBG-P4E	7/C	10	0.030	0.8	0.060	1.5	0.666	16.9	411	612	581	264	8.0	203	28
	8201008BBG-P4E	8/C	10	0.030	0.8	0.060	1.5	0.719	18.3	460	685	664	301	8.6	219	28
	8201009BBG-P4E	9/C	10	0.030	0.8	0.060	1.5	0.745	18.9	506	753	747	339	8.9	227	28
8201010BBG-P4E	10/C	10	0.030	0.8	0.060	1.5	0.778	19.8	552	822	830	377	9.3	237	28	
8201011BBG-P4E	11/C	10	0.030	0.8	0.060	1.5	0.807	20.5	598	890	913	414	9.7	246	28	
8201012BBG-P4E	12/C	10	0.030	0.8	0.080	2.0	0.877	22.3	678	1009	996	452	10.5	267	28	
8201015BBG-P4E	15/C	10	0.030	0.8	0.080	2.0	0.976	24.8	821	1223	1245	565	11.7	298	28	
8201020BBG-P4E	20/C	10	0.030	0.8	0.080	2.0	1.107	28.1	1055	1570	1660	753	13.3	337	28	
8201025BBG-P4E	25/C	10	0.030	0.8	0.080	2.0	1.232	31.3	1289	1919	2075	941	14.8	376	24	
8201030BBG-P4E	30/C	10	0.030	0.8	0.080	2.0	1.303	33.1	1513	2252	2490	1130	15.6	397	24	
8201040BBG-P4E	40/C	10	0.030	0.8	0.080	2.0	1.458	37.0	1963	2922	3320	1506	17.5	444	24	
8201050BBG-P4E	50/C	10	0.030	0.8	0.080	2.0	1.622	41.2	2414	3593	4150	1883	19.5	494	20	

Ampacity values based on CE Code Part I 2021, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 230, Tray Cables
- CSA C22.2 No. 2556 FT4, IEEE 1202/UL 1865
- 40°C Cold Bend and -40°C Cold Impact
- SUN RES all colours

Conductor	Stranded Bare Soft Copper, ASTM B8
Insulation	Cross-linked Polyethylene Insulation (XLPE) CSA Type XL 90°C dry/wet 600V
Jacket	Low Acid Gas Polyvinyl Chloride (PVC)
Colour Code	Black, White, Red and Blue or Black with White printed number
Bonding	Green Insulated Stranded Bare Soft Copper, ASTM B8

Applications

- For wet and dry locations.
- For use in raceways, including cable trays, Ventilated, non-ventilated, ladder tray and direct burial.
- To be used for exposed and concealed wiring or where subjected to the weather.
- For Hazardous Locations Class I-Zone 0 Intrinsically safe Div. 2, Class II-Zone 2 Div. 2 and Class III-Div. 2.
- Cables marked TC-ER tray cable are permitted to transition between cable trays, and utilization equipment or devices as per CE Code Part I 12-2202 2) and 3).

